

CIRANOVA® LACQUER - SYSTEM


PREPARATION (OPTIONAL)

1

WOOD FILLER GEL

PRIMING COAT (OPTIONAL)


2

	ECOFIX WOODLOOK Bleaching primer	FORTICO SEALER
coats	1	1
	+/- 4 à 6h	+/- 3h

Don't sand the priming coat !

PROTECTION - LACQUER

3

	FORTICO 1C - MATT / SATIN FORTICO 2C - MATT / SATIN / NATURAL
coats	2 (when using a priming coat) 3 (When you don't use a priming coat)
	First coat : +/- 3 h Second coat : +/- 6 h <i>Slightly sand with P180-220 before applying the last coat</i> Third coat.: +/- 12 h

MAINTENANCE

4

HARD FLOOR
FRESH



HARD FLOOR
CLEANER



• HARD FLOOR POLISH
• UNICARE X-MATT



It is recommended to consult the technical data sheet of the product for info about the application and specific properties.



HIGH QUALITY WOODCARE PRODUCTS

Produced by Debal Coatings nv
 Industrierweg 29 - 8800 Beveren Roeselare - Belgium
 tel +32 (0)51 30 11 40 | fax +32 (0)51 31 26 48 | ciranova@ciranova.be
www.ciranova.eu

03/2017