

# ECOFIX PLUS

ECOFIX PLUS is an invisible, 35% Bio-based, environmentally friendly, water-based PU impregnating oil for parquet and wooden furniture. The wood will have an untreated and ultra matte appearance. ECOFIX PLUS is non-yellowing and has anti-slip properties.

- » **Ultimate invisible finish**
- » Gives an untreated appearance
- » Very easy to apply
- » Non-Yellowing



### PREPARATION

Make sure all prior coatings are completely removed and the wood surface is free from dust and other contamination. Can be used on sanded, planed and brushed wood.

### APPLICATION

ECOFIX PLUS can be used both as a primer and as a finishing coat. It can be applied in three coats. Stir thoroughly before use and do not dilute. Apply the product using a roller or brush. A short-pile roller is recommended (microfiber 4-6mm). Contact Ciranova technical support for spray application. Apply the first coat in the direction of the wood. After 4-6 hours, apply a second coat in the same way as the first coat. Let dry for 12-24 hours and afterwards do an intermediate sanding using grit 180-220, then apply the third coat.

### DRYING TIMES

Touch dry: after 20 to 30 minutes.  
 Sandable : after 4 to 6 hours.  
 Lightly walkable: after 24 hours  
 The drying times are highly dependent on the applied quantity, temperature, humidity and ventilation.

### MAINTENANCE

Regular maintenance with Hard Floor Fresh Ciranova®. Use UNICARE X-MATT for periodic maintenance. Hard Floor Cleaner Ciranova® is used for cleaning highly soiled floors and to remove old layers of polish.

## TECHNICAL DATA

<b>Product type</b>	waterborne
<b>Cleaning</b>	water
<b>Gloss level</b>	Invisible
<b>Viscosity</b>	+/-25 sec - DIN 4mm
<b>Solids content</b>	+/- 31%
<b>Sold by case</b>	4 x 5 L 6 x 1 L
<b>Coverage</b>	10-12 m <sup>2</sup> /liter per coat 100-130 sq.ft./L per coat
<b>Drying times</b>	Dust dry: after 20 to 30 minutes Sandable: after 4 to 6 hours lightly walkable: after 24 hours Fully cured: after +/- 7 days
<b>Sanding grit</b>	P 120-150
<b>Storage/transport</b>	between 5°C and 25°C
<b>Shelf life</b>	12 months in the original and unopened packaging.
<b>Disposal</b>	Dispose of residue and empty packaging in accordance with local ordinances.

### IMPORTANT INFORMATION ▲

Only use non-corrosive materials. Clean all materials with water immediately after use. If the wood needs to be stained first, only use Ciranova® Aquapad + 10% Aquapad Hardener. For exotic types of wood, the finishing should be tested in advance. For industrial application, please consult Ciranova® technical support.

**Water-based products can develop skins after contact with air. Filter beforehand, if necessary.**

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However they are drawn to our best knowledge and ability, the user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.