

## DECKING OIL

Impregnation oil for the protection and maintenance of all exterior wood. DECKING OIL has a built-in UV blocker that slows down discoloration of the wood. DECKING OIL nourishes and protects the wood and provides a water-resistant effect.

- » Easy to apply on all wooden patios and decking.
- » A built-in UV blocker ensures that the wood does not age as fast.



PROTECTION

OUTDOOR

2,5L



### PREPARATION

Before applying DECKING OIL, first clean the wood with WOODCLEANER or DEGREYER Ciranova®. Make sure that all dirt is removed before application of the DECKING OIL.

### APPLICATION

Apply DECKING OIL with a brush or pad in the direction of the boards. Let dry and remove the excess oil within 15 minutes by polishing with a white pad or cloth. After 12 hours apply a second layer in the same way as the first layer. Make sure the wood is well saturated for a long term protection. When using DECKING OIL on furniture, make sure the excess oil is rubbed out until the surface feels fully dry.

### MAINTENANCE

To obtain a longer life of the wood, its recommended to apply 1 or 2 a year a new coat of DECKING OIL. First clean with Ciranova® WOODCLEANER before applying a new coat of DECKING OIL.

## TECHNICAL DATA

### Product type

solvent-based

### Cleaning

Cleaning Thinner Ciranova®

### Solid content

+/- 57%

### Coverage

20-24 m<sup>2</sup>/liter

### Number of colors

EU: 8 colors

### Drying times

paintable after: 4 to 6 hours

dry after: +/- 24 hours

### Sanding grit

P 100

### Storage/transport

between 5°C and 25°C

### Disposal

dispose of residue and empty packaging in accordance with local ordinances.