

## QUALITY WAX

Traditionally manufactured floor wax based on natural raw materials, such as carnauba, candelilla, raw bees wax and Portuguese turpentine oil for the protection of wooden furniture.

- » Traditionally manufactured floor wax.
- » Gives the wood an authentic finish.

### TECHNICAL DATA

#### Product type

solvent-based

#### Cleaning

wax remover

#### Solid content

+/- 30%

#### Number of colors

colorless, yellow and brown,  
\*medium, \*dark, \*mahonie

#### Coverage

ca. 7-12 m<sup>2</sup>/liter per layer

#### Drying times

12 hours

#### Storage/transport

between 5°C and 25°C

#### Disposal

dispose of residue and empty packaging in accordance with local ordinances.



Only in medium, dark, antique, yellow

0,5kg

1kg

5kg



### PREPARATION

Make sure that all old finish coats are completely removed and that the wood is free from dust and other dirt. Can be used on sanded, planed and brushed wood.

### APPLICATION

Apply a thin coat with a sponge, brush or cloth. After drying polish with a soft cloth. Multiple coats increase the gloss level.

### FINISHING

QUALITY WAX can be used as a primer and finishing coat. **ATTENTION: never apply a varnish or oil after use of the QUALITY WAX.**

### MAINTENANCE

QUALITY WAX can be cleaned with WAX REMOVER. Afterwards, apply a layer of LIQUID FLOORING WAX as a finishing coat.

### IMPORTANT INFORMATION ⚠

ATTENTION: Never apply a varnish or oil after use of the QUALITY WAX.