

FLOORING WAX

A traditional water repellent flooring wax made from natural and synthetic waxes for the protection of wooden floors. A silicone resin improves the water repellency.

- » Natural protection based on natural and synthetic waxes.
- » Gives the wood an authentic finish.

TECHNICAL DATA

Product type

solvent-based

Cleaning

wax remover

Solid content

+/- 25%

Number of colors

colorless, yellow and brown

Coverage

ca. 7 -12 m²/liter

Drying times

12 hours

Sanding grit

P 100-120

Storage/transport

between 5°C and 25°C

Disposal

dispose of residue and empty packaging in accordance with local ordinances.



1L

5L



PREPARATION

Make sure that all old finish coats are completely removed and that the wood is free from dust and other dirt. Sanding using the correct method : deep sanding with 60-80-100 grit then sanding with 100 grit. Can be used on sanded, planed, and brushed wood. For a better water-resistance, HARDWAXOIL can be used as a primer first.

APPLICATION

Apply a thin coat with a sponge, brush, cloth or buffing machine. Afterwards polish with a cloth or white pad. After drying you can buff again with a soft cloth or white pad. Multiple coats increase the gloss level.

FINISHING

FLOORING WAX can be used as a primer and finishing coat.

MAINTENANCE

FLOORING WAX can be cleaned with WAX REMOVER. Afterwards, apply a layer of LIQUID FLOORING WAX as a finishing coat.

IMPORTANT INFORMATION ⚠

ATTENTION: Never apply a varnish or oil after use of the FLOORING WAX.