

ECOFIX ROLL

PRODUCT DESCRIPTION:

ECOFIX ROLL is a water based impregnation oil for parquet and wooden furniture. The wood retains its original and untreated appearance. To be used as a primer.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.
Only for interior use

TECHNICAL DATA

extra component:	-
mixing ratio:	-
pot-life:	-
density:	1.03 KG/L
viscosity:	ca 20 sec DIN 8 20°C
colors:	Milky
solid content:	ca 36%
gloss:	CA 15 Gu at 60°
thinner:	water
coverage per coat:	ca 30g/m ²
Coverage USA per coat:	ca 3g/ft ²
drying:	3hrs – 4hrs at room temperature. Forced drying possible.

APPLICATION MATERIAL



PACKING

5lt -20lt



APPLICATION

preparation substrate: Prepare the wood according the rules of the art and remove the sanding dust carefully

processing:

- stir well before use.
- stain the wood if required with REACTIVE STAINS or waterbased stains.
- application quantity : ca 30g/m²

PROTECTION

Natural Oils, UV Oils, Lacquers

IMPORTANT INFORMATION

Ecofix Rollskins fast in contact with air, if necessary filter before use.

- it is recommended to first make a test on the wood before starting the production.
- be aware of discoloration or delamination because of the substances in the wood or special wood species.
- use only stainless material.
- After use, rinse the material directly with Hydro Cleaner and water.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 – 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"