

## OCULTO ROLL

### PRODUCT DESCRIPTION:

OCULTO ROLL is a PU waterbased ecological impregnating oil for parquet and wooden furniture. The wood retains its original, natural look and is invisible. It also contains UV-inhibitors. To be used as a primer.

### RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.

Only for interior use

### CERTIFICATES/LABELS:

antislip R9 / CpdH / A+ (Fr) / AgBB / Belgian indoor Pass

### TECHNICAL DATA

<b>extra component:</b>	-
<b>mixing ratio:</b>	-
<b>pot-life:</b>	-
<b>density:</b>	1.03 KG/L
<b>viscosity:</b>	ca 20 sec DIN 8 20°C
<b>colors:</b>	Milky
<b>solid content:</b>	ca 29%
<b>gloss:</b>	<5 gU at 60°
<b>thinner:</b>	water
<b>coverage per coat:</b>	ca 30g/m <sup>2</sup>
<b>Coverage USA per coat:</b>	ca 3g/ft <sup>2</sup>
<b>drying:</b>	3hrs – 4hrs at room temperature. Forced drying possible.

### APPLICATION MATERIAL



### PACKING

5lt -20lt



### APPLICATION

**preparation substrate:** Prepare the wood according the rules of the art and remove the sanding dust carefully

**processing:**

- stir well before use.
- stain the wood if required with REACTIVE STAINS or waterbased stains.
- application quantity : ca 30g/m<sup>2</sup>

### PROTECTION

Natural Oils, UV Oils, Lacquers or Oculito

### IMPORTANT INFORMATION

OCULTO Roll skins fast in contact with air, if necessary filter before use.

- it is recommended to first make a test on the wood before starting the production.
- be aware of discoloration or detachment because of the substances and special wood species.
- use only stainless material.
- After use, rinse the material directly with Hydro Cleaner and water.

### SHELF-LIFE

In well-closed and original packing: minimum 12 months

### WAREHOUSING

by 10 – 40 °C

### CLEANING

HYDRO CLEANER 7984

### ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"