

## AQUACOLOR

### PRODUCT DESCRIPTION:

Aquacolor is a water based wood stain, especially made for uniform wood staining.

This product is light stable and not reactive

### RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.

Only for interior use

### TECHNICAL DATA

<b>extra component:</b>	-
<b>mixing ratio:</b>	-
<b>pot-life:</b>	-
<b>density:</b>	DEPENDS ON THE COLOR
<b>viscosity:</b>	-
<b>colors:</b>	16 STANDARD colors available. Other colors on demand.
<b>solid content:</b>	depending on the color
<b>gloss:</b>	-
<b>thinner:</b>	Clear Stain AQC 7520
<b>coverage per coat:</b>	20 - 50g/m <sup>2</sup>
<b>Coverage USA per coat:</b>	2 - 5g/ft <sup>2</sup>
<b>drying:</b>	3hrs - 4hrs at room temperature. Forced drying possible.

### APPLICATION MATERIAL



### PACKING

5lt - 25lt

### APPLICATION

<b>preparation substrate:</b>	Prepare the wood according the rules of the art and remove the sanding dust carefully
<b>processing:</b>	- Stirr well before use. - Spraying : apply +/- 50g/m <sup>2</sup> , even outing with a dry brush, air- or forced drying - Manual application : apply the Aquacolor generously with a brush in the direction of the wood fiber, even outing afterwards with brush or cloth, air- or forced drying - roller application: Apply the Aquacolor by a soft roller ca 20g/m <sup>2</sup> , even outing with a dry brush, air- or forced drying

### PROTECTION

The aquacolor can be protected with UV Oil, Natural Oil, waxes and lacquer

### IMPORTANT INFORMATION

The final color depends on the type of wood, sanding, wood preparation and the applied quantity. For this reason its always recommended to make a test first before starting production.

- Only use stainless material.
- Clean all material immediately after use.

### SHELF-LIFE

In well-closed and original packing: minimum 12 months

### WAREHOUSING

by 10 - 40 °C

### CLEANING

HYDRO CLEANER 7984

#### ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"