

ATOLL MILK

PRODUCT DESCRIPTION:

ATOLL MILK is a special liquid that gives a rustical liming effect.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.
Only for interior use

TECHNICAL DATA

extra component:	-
mixing ratio:	-
pot-life:	-
density:	1.54 KG/L
viscosity:	cream / pasty
colors:	OFF-WHITE
solid content:	????
gloss:	-
thinner:	water
coverage per coat:	ca 50g/m ²
Coverage USA per coat:	ca 5 g/ft ²
drying:	3hrs – 4hrs at room temperature. Forced drying possible.

APPLICATION MATERIAL



PACKING

5lt - 25lt



APPLICATION

preparation substrate: Prepare the wood well by sanding or brushing. Brush the woodgrains carefully, remove the dust. Apply Atoll Milk on rough prepared wood or stained wood.

processing: Stir well, apply on the surface approx. 50gr/m².
Dry on room temperature or dry with hot air oven.
Remove the excess of dust if needed.

PROTECTION

UV oil or Hardwax oil Magic finish.
For UV oil finish seal first the atoll dust surface with Ecofix or Oculito.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 – 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"