

HARDWAXOIL TITAN

PRODUCT DESCRIPTION:

Hardwaxoil TITAN is a special oil suitable for oil finishing of wooden floors. Good filling properties, very natural color, good chemical and mechanical resistance. The Hardwaxoil TITAN has a long open time which makes it very appropriate to apply by roller and rollercoater.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels. Only for interior use

CERTIFICATES/LABELS:

Indoor Air comfort

TECHNICAL DATA

extra component:	HARDENER UA
mixing ratio:	100:5
pot-life:	CA 6 HRS
density:	depending on color
viscosity:	ca. 50 sec DIN 4 (at 20°C)
colors:	CLEAR
solid content:	ca 46%
gloss:	Matt - Silk - Satin
thinner:	Oil Retarder
coverage per coat:	ca 20 - 25g/m ²
Coverage USA per coat:	ca 2 - 2.5g/ft ²
drying:	Can be overcoated after +/- 6 - 12 Hours. The drying time is very dependent on the applied quantity, the temperature and air ventilation in the room.

APPLICATION MATERIAL



PACKING

5L - 25L



APPLICATION

preparation substrate: Prepare the wood according to the rules of the art and remove the sanding dust carefully

processing: Mix the oil with the hardener (100:5) and let the product rest for about 10 minutes.
When needed color the wood with stains from Ciranova Industrial Finishes.
Can be applied with a roller coater. Use brushes to remove marks.
After drying, a second or even a third coat is recommended.

MAINTENANCE

Please consult the maintenance program from Ciranova.

IMPORTANT INFORMATION

Used cloths or pads should be plunged in water because of the danger of spontaneous combustion. We recommend Hardwaxoil Titan as topcoat on the pigmented Hardwaxoils. Colored Hardwaxoils should always be tested before treating the entire surface.
Used sanding grain, type of wood, may affect the final color.

SHELF-LIFE

In well-closed and original packing: minimum 24 months

WAREHOUSING

by 10 – 40 °C

CLEANING

COMBI CLEANER 2879

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"