

OCULTO

PRODUCT DESCRIPTION:

OCULTO is a PU waterbased ecological impregnating oil for parquet and wooden furniture. The wood retains its original, natural look and is invisible. It also contains UV-inhibitors

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels.

Only for interior use

CERTIFICATES/LABELS:

antislip R9 / CpdH / A+ (Fr) / AgBB / Belgian indoor Pass

TECHNICAL DATA

extra component:	Optional: Hardener Oculito
mixing ratio:	10:1
pot-life:	3 - 4hrs
density:	1.03 KG/L
viscosity:	+/- 16 SEC (DIN 4MM)
colors:	Milky
solid content:	ca 29%
gloss:	<5 gU at 60°
thinner:	water
coverage per coat:	ca 50g/m ²
Coverage USA per coat:	ca 5g/ft ²
drying:	3hrs - 4hrs at room temperature. Forced drying possible.

APPLICATION MATERIAL



PACKING

5lt -25lt

APPLICATION

preparation substrate: Prepare the wood according to the rules of the art and remove the sanding dust carefully

processing:

- stir well before use.
- stain the wood if required with REACTIVE STAINS or waterbased stains.
- application quantity : 50 - 60 g/m².

PROTECTION

Natural Oils, UV Oils, Lacquers or Oculito

IMPORTANT INFORMATION

OCULTO skins fast in contact with air, if necessary filter before use.

- it is recommended to first make a test on the wood before starting the production.
- be aware of discoloration or detachment because of the substances and special wood species.
- use only stainless material.
- After use, rinse the material directly with Hydro Cleaner and water.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 - 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"