

OCULTO SPRAY

PRODUCT DESCRIPTION:

OCULTO SPRAY is a waterbased ecological impregnating oil for parquet and wooden furniture. The wood retains its original, natural look and is invisible. Oculito Spray is an anti-slip finish and has UV-inhibitors. Can be used as multilayer system there where several coats are necessary. Optional, a hardener (100:10) can be added for improved durability. Resistant against most cleaning products.

RANGE OF APPLICATION:

Industrial application for wooden staircases and parquet, as well as chairs, furniture and other wooden objects for vertical and horizontal applications. OCULTO SPRAY has special anti-slip characteristics.

TECHNICAL DATA

extra component:	HARDENER OCULTO
mixing ratio:	10:1
pot-life:	3 - 4 HRS
density:	1.03 KG/LT
viscosity:	With hardener: ca. 35" DIN 6 (20°C)
colors:	CLEAR
solid content:	ca 29%
gloss:	ULTRA MATT
thinner:	WATER
coverage per coat:	80 - 100g/m ²
Coverage USA per coat:	8 - 10g/ft ²
drying:	3hrs - 4hrs at room temperature. Forced drying possible.

PACKING

25lt



APPLICATION MATERIAL



APPLICATION

- preparation substrate:** Prepare the wood according to the rules of the art and remove the sanding dust carefully
- processing:** Add hardener (100:10) and stir well before use.
Sand the wooden substrate with grain P180-P220.
When needed color the wood with stains from Ciranova Industrial Finishes.
Depending on the kind of wood, application and intended aspect, apply 2 or 3 coats with intermediate sanding P280 - P320.

MAINTENANCE

Please consult the maintenance programm from Ciranova.

IMPORTANT INFORMATION

- Water based products skins fast in contact with air, if necessary filter before use.
- it is recommended to first make a test on the wood before starting the production.
 - be aware of discoloration or detachment because of the substances and special wood species.
 - use only stainless material.
 - After use, rinse the material directly with Hydro Cleaner and water.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 - 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"