

UV BASE TINTERS

PRODUCT DESCRIPTION:

TINTERS used for UV oils. Natural oil, modified acrylics, can be used as a tinted basecoat. Good adhesion on wood. Coloring of the wood. Low film build. Gives a perfect look as a traditional oiled wooden floor.

RANGE OF APPLICATION:

Industrial Tinting system for tinting UV curing products.

TECHNICAL DATA

extra component:	HARDENER UV OIL 8388
mixing ratio:	100:4
pot-life:	ca 8 hours
density:	Depending on color
viscosity:	DEPENDS ON THE COLOR
colors:	10 TINTERS AVAILABALE
solid content:	+96%
gloss:	-
thinner:	-
coverage per coat:	ca 15g/m ²
Coverage USA per coat:	ca 1.5g/ft ²
drying:	UV Curing

APPLICATION MATERIAL



PACKING

1kg - 5kg



APPLICATION

preparation substrate:

-

processing:

All tinters are inter mixable without restriction.
For processing, please follow the the processing of UV oil COLOR.

PROTECTION

UV OIL CLEAR

IMPORTANT INFORMATION

- The use of coatings containing isocyanates demands convenient precautions (see MSDS).
- Avoid sanding the first coat by gelling the film with low energy UV lamps.
- The added hardener will help to cure the UV Oil also in the wood where the UV lamps cannot reach.
- The hardener will also improve the adhesion, resistance to water and other chemical products.

SHELF-LIFE

In well-closed and original packing: minimum 9 months

WAREHOUSING

by 10 – 40 °C

CLEANING

COMBI CLEANER 2879

ATTENTION ⚠

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"