

TECHNICAL DATA SHEET

P. 11

VINTAGE COLORS

PRODUCT DESCRIPTION:

Ciranova Vintage is a waterborne reaction stain to give a weathered 'vintage' look to wood that contains tannin.

RANGE OF APPLICATION:

Industrial application for Wood Flooring and wood panels. Only for interior use

APPLICATION

preparation substrate: the sam

processing:

 Prepare the wood according the rules of the art and remove the sanding dust carefully
 Stir before use and mix separate batches to ensure the color

consistency.
Do not work out of the container.
Use a sprayer and apply a generous coat around 50 - 60g/m²
even out out in the direction of the grain.

off the excess of pigments with a scotch-brite or light sanding.

PROTECTION

Afterwards the Vintage color can be protected with UV Oil, Natural Oil or wax

IMPORTANT INFORMATION

· Respect reaction time.

• The final color depends on the type of wood, sanding, wood preparation and the applied quantity. For this reason its always recommended to make a test first before starting production.

- Only use stainless material.

- Clean immediately after use. BE CAREFULL: the product is corrosive.

BE CAREFULL: the product is corrosive.

SHELF-LIFE

In well-closed and original packing: minimum 12 months

WAREHOUSING

by 10 – 40 °C

CLEANING

HYDRO CLEANER 7984

TECHNICAL DATA

extra component:	-
mixing ratio:	-
pot-life:	-
density:	depending on the color
viscosity:	as water
colors:	5 colors available
solid content:	depending on the color
gloss:	-
thinner:	-
coverage per coat:	ca 50g/m ²
Coverage USA per coa	t: $ca 5 g/ft^2$
drying:	reaction time: minimum 6 hrs

APPLICATION MATERIAL



PACKING 5lt - 25lt



ATTENTION **A**

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"