

TECHNICAL DATA SHEET

WOODFILLER FAST

PRODUCT DESCRIPTION:

Wood Filler Fast is an ecological Wood filler. The product is odourless, not flammable and not toxic. Dries very fast without shrinking and can fill cracks untill 8 mm depth.

RANGE OF APPLICATION:

Reparation of cracks and holes in all types of wood and for all woodwork such as furniture and parquet floors.
Only for interior use

TECHNICAL DATA

extra component: Water mixing ratio: 40:10 ca 40 min.

density:

colors: light Oak 7359; Dark 7360; Black 7363

solid content: 100% gloss: - water

coverage per coat: depending on the knots **Coverage USA per coat:** depending on the knots **drying:** Sandable: after 30 min. - 2 hours

(depending on the size of the reparation). Completely hardened after 24 hours. Drying time can be limited with higher temperatures and

increased air ventilation.

PACKING

5kg



APPLICATION

preparation substrate: Sand the surface well before

treatment, remove loose pieces,

make dust-free.

processing: Choose the color most conform for

the wood to be treated. Dilute the powder with clean cold water. Proportion: 1 part of water on 3 parts

of powder.

Mix well and wait for approximately 5 min. in order to become a

homogenous paste.

After preparation of the paste, the mixture can be used for about 40 minutes. Irregulations in the surface can be removed till 8 mm depth in

1 layer.

For larger reparations, this treatment

has to be repeated.

PROTECTION

After drying, first sand the Wood Filler smoothly and finish with oil, varnish or wax.

IMPORTANT INFORMATION

Respect the requested proportions for the quantities that you need. Wood Filler is biodegradable and is classified as a non-dangerous product. This product is not flammable

SHELF-LIFE

In well-closed and original packing, if not prepared, minimum 12 months.

WAREHOUSING

by 10 - 40 °C

CLEANING

HYDRO CLEANER 7984

ATTENTION A

"All tests and application methods are done with the above-mentioned Debal Coatings components. We are not responsible for application with other materials, unless written agreement from Debal Coatings"