

FORTICO 1C SATIN MATT - NATURAL

Excellent water-based PU sealer for parquet with moderate traffic. FORTICO 1C has very high chemical and mechanical resistance. Easy application with no overlaps or roller marks. FORTICO 1C is used for finishing parquet and floors in single-family homes and other areas subject to moderate wear.

- » Highly scratch-resistant thanks to anti-scratch technology.
- » High wear resistance.
- » Does not glare.

TECHNICAL DATA

Product type

water-based

Cleaning tools

water

Gloss level

Matt 10-15; Satin 35-50; Natural <5

Viscosity

+/-25 sec - DIN 4mm

Packaging

6 x 1 l

4 x 5 l

Coverage

10-12m²/litre per coat

Drying/reaction time

Touch-dry after 2 hours.

Can be sanded after: 3 to 5 hours

Light traffic after 12 hours

Fully cured after 7 to 10 days.

Abrasive grain

P 120-150

Transport

between 5°C and 25°C

Waste

Dispose of residues and empty packaging in accordance with local regulations.



1L

5L



PRELIMINARY TREATMENT

Make sure that all old finishing coats are removed and that the floor is clean and free of residues. Sand using the correct method: deep sanding with 60-80-100 grit, followed by abrasive sanding with 100 grit. Can be used on planed, sanded and brushed wood. For a lighter, more natural finish, you can first use FORTICO 1C NATURAL as a base coat. For floors with underfloor heating, exotic woods and cork, we recommend FORTICO SEALER as a base.

APPLICATION

Use FORTICO 1C as both a base and top coat. Apply the 3 coats of the product using a spalter brush or roller (8 mm microfibre).

First coat: apply approx. 10 m²/l and allow to dry for +/- 3 hours.

Second coat: apply approximately 10 m²/l in the same way as the first coat and allow to dry for +/- 3 hours. Next, sand with 120-150 grit paper, remove dust and apply a third coat covering approximately 10 m²/l.

DRYING TIME

Light traffic after 12 hours.

Fully cured after 7 to 10 days.

Drying times are highly dependent on the quantity applied, ambient temperature, humidity and ventilation.

FURTHER TREATMENT

FORTICO 1C can be used as a base and a top coat.

MAINTENANCE

Maintain regularly with HARD FLOOR FRESH Ciranova®. For periodic maintenance, use HARD FLOOR POLISH Ciranova® or UNICARE X-MATT Ciranova®. HARD FLOOR CLEANER Ciranova® is used to clean heavily soiled floors and remove old coats of varnish.

IMPORTANT INFORMATION ⚠

Use stainless steel/rustproof equipment only. Clean all tools and equipment with water immediately after use. For industrial applications, please contact the Ciranova technical service®. Water-based products can form a film on contact with air. Pre-filter the product if necessary.