

EXTERIOR BARE WOOD PRIMER

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

>SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : EXTERIOR BARE WOOD PRIMER
UFI : 15EG-N4JS-P006-F9EJ

> 1.2. Relevant identified uses of the substance or mixture and uses advised against

consumer use
professional use

1.3. Details of the supplier of the safety data sheet

Registered company name : BLANCHON UK.Limited.
Address : Brenchley House, School Road.TN27 0JW.Charing, Kent .United Kingdom.
Telephone : +44 7379 962 642 . Fax : .
fds@blanchon.com
www.ciranova.eu
Head Office - DEBAL COATINGS NV - Industrieweg 29 - 8800 Beveren-Roeselare - Belgium

1.4. Emergency telephone number : +844 892 0111.

Association/Organisation : National Poisons Information Service (Birmingham Unit).

Other emergency numbers

National Poisons Information Service (Birmingham Unit) : 844 892 0111
Poisons Information Centre of Ireland (DUBLIN) : +353 1 809 25 66 or +353 1 837 9964 (medical professionals)

>SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Eye irritation, Category 2 (Eye Irrit. 2, H319).
May produce an allergic reaction (EUH208).
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

> In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS07

Signal Word :

WARNING

Additional labeling :

EUH208
EUH208

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.
Contains MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ;
2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

Hazard statements :

H319

Causes serious eye irritation.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P271

Use only outdoors or in a well-ventilated area.

Precautionary statements - Disposal :

P501

Dispose of contents / container to an approved landfill.

EXTERIOR BARE WOOD PRIMER

> 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

Contains biocidal products (in-can preservative) : Contains MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) (CAS No. 55965-84-9) and 1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS No. 2634-33-5) and 3-iodo-2-propynyl butylcarbamate (CAS No. 55406-53-6).

>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

> Composition :

Identification	Classification (EC) 1272/2008	Note	%
CAS: 2226-96-2 EC: 218-760-9 REACH: 01-2119968566-20 4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINE NYLOXY	GHS07, GHS05, GHS08 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 STOT RE 2, H373		1 $\leq x \% < 2.5$
INDEX: 603-052-00-8 CAS: 5131-66-8 EC: 225-878-4 REACH: 01-2119475527-28 3-BUTOXYPROPAN-2-OL	GHS07 Wng Eye Irrit. 2, H319 Skin Irrit. 2, H315		1 $\leq x \% < 2.5$
INDEX: 616-212-00-7 CAS: 55406-53-6 EC: 259-627-5 3-iodo-2-propynyl butylcarbamate	GHS06, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 STOT RE 1, H372 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 $\leq x \% < 1$
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH: 01-2120761540-60 1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS06, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 $\leq x \% < 0.036$
INDEX: 613-167-00-5 CAS: 55965-84-9 REACH: 01-2120764691-48 MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	GHS06, GHS05, GHS09 Dgr Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 M Acute = 100 Aquatic Chronic 1, H410 M Chronic = 100 EUH071	B	0 $\leq x \% < 0.0015$

EXTERIOR BARE WOOD PRIMER

> Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 2226-96-2 EC: 218-760-9 REACH: 01-2119968566-20 4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINE NYLOXY		oral: ATE = 1053 mg/kg BW
INDEX: 616-212-00-7 CAS: 55406-53-6 EC: 259-627-5 3-iodo-2-propynyl butylcarbamate		inhalation: ATE = 0.17 mg/l 4h (dust/mist)
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 REACH: 01-2120761540-60 1,2-benzisothiazol-3(2H)-one	Skin Sens. 1A: H317 C>= 0.036%	inhalation: ATE = 0.21 mg/l 4h (dust/mist) oral: ATE = 450 mg/kg BW
INDEX: 613-167-00-5 CAS: 55965-84-9 REACH: 01-2120764691-48 MIXTURE OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE ; 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	Skin Corr. 1C: H314 C>= 0.6% Skin Irrit. 2: H315 0.06% <= C < 0.6% Eye Dam. 1: H318 C>= 0.6% Eye Irrit. 2: H319 0.06% <= C < 0.6% Skin Sens. 1A: H317 C>= 0.0015%	

Information on ingredients :

(Full text of H-phrases: see section 16)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

EXTERIOR BARE WOOD PRIMER

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Dermal contact.

Long term systemic effects.

52 mg/kg body weight/day

EXTERIOR BARE WOOD PRIMER

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 147 mg of substance/m3

Final use:

Exposure method: **Consumers.**
Potential health effects: Ingestion.
DNEL : Long term systemic effects.
12.5 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 22 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 43 mg of substance/m3

4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINYLOXY (CAS: 2226-96-2)

Final use:

Exposure method: **Workers.**
Potential health effects: Dermal contact.
DNEL : Long term systemic effects.
0.3 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 8 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 1.2 mg of substance/m3

Final use:

Exposure method: **Consumers.**
Potential health effects: Ingestion.
DNEL : Long term systemic effects.
0.2 mg/kg body weight/day

Exposure method: Ingestion.
Potential health effects: Short term systemic effects.
DNEL : 4 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 0.2 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Short term systemic effects.
DNEL : 4 mg/kg body weight/day

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 0.3 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Short term systemic effects.
DNEL : 7 mg of substance/m3

Predicted no effect concentration (PNEC):

3-BUTOXYPROPAN-2-OL (CAS: 5131-66-8)

Environmental compartment: Fresh water.
PNEC : 0.525 mg/l

Environmental compartment: Sea water.

EXTERIOR BARE WOOD PRIMER

PNEC :	0.0525 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 5.25 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 2.36 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.236 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l

4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINYLOXY (CAS: 2226-96-2)

Environmental compartment: PNEC :	Soil. 0.031 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.03 mg/l
Environmental compartment: PNEC :	Sea water. 0.003 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.54 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.126 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.0169 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 430 mg/l

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard ISO 16321.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

EXTERIOR BARE WOOD PRIMER

- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****Physical state**

Physical state : Fluid liquid.

Colour

Colorless

Odour

Odour threshold : Not stated.
low odour

Melting point

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : 100 °C.

> Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash Point Interval : FP > 100°C.

Auto-ignition temperature

Self-ignition temperature : Not specified.

> Decomposition temperature

Decomposition point/decomposition range : Not specified.

> pH

pH : Not stated.

Slightly basic.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Dilutable.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative density

Density : > 1

Relative vapour density

Vapour density : Not stated.

Particle characteristics

The mixture does not contain nanoforms.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

EXTERIOR BARE WOOD PRIMER

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

>SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1. Substances

> a) Acute toxicity :

3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS: 55406-53-6)

Inhalation route (Dusts/mist) :

LC50 = 0.17 mg/l

Duration of exposure : 4 h

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

Oral route :

LD50 = 450 mg/kg body weight

Inhalation route (Dusts/mist) :

LC50 = 0.21 mg/l

Duration of exposure : 4 h

4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINYL OXY (CAS: 2226-96-2)

Oral route :

LD50 = 1053 mg/kg body weight

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route :

LD50 > 2000 mg/kg body weight

Species : Rat

OECD Guideline 402 (Acute Dermal Toxicity)

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

No data available.

d) Respiratory or skin sensitisation :

No data available.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

EXTERIOR BARE WOOD PRIMER

j) Aspiration hazard :

No data available.

11.1.2. Mixture

11.1.2.1 Information on hazard classes

|> a) Acute toxicity :

Oral route : No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) : No data available.

b) Skin corrosion/skin irritation :

No data available.

c) Serious damage to eyes/eye irritation :

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

d) Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

e) Germ cell mutagenicity :

No data available.

f) Carcinogenicity :

No data available.

g) Reproductive toxicant :

No data available.

h) Specific target organ systemic toxicity - single exposure :

No data available.

i) Specific target organ systemic toxicity - repeated exposure :

No data available.

j) Aspiration hazard :

No data available.

11.1.2.2 Other information

11.2. Information on other hazards

No other hazards known according to Regulation (EC) No 1272/2008

Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINYLOXY (CAS: 2226-96-2)

Fish toxicity :

LC50 = 545 mg/l

Species : Brachydanio rerio

Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity :

EC50 = 54 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity :

ECr50 = 1038 mg/l

Species : Scenedesmus subspicatus

Duration of exposure : 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

EXTERIOR BARE WOOD PRIMER

12.2. Persistence and degradability

12.2.1. Substances

4-HYDROXY-2,2,6,6-TETRAMETHYL-1-PIPERIDINYLOXY (CAS: 2226-96-2)
Biodegradability : Non-rapidly degradable.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

15 01 10* packaging containing residues of or contaminated by hazardous substances

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Maritime transport in bulk according to IMO instruments

-

>SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

> Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2025/1222. (ATP 23)

EXTERIOR BARE WOOD PRIMER

Container information:

No data available.

Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 50 g/l.

The permitted European levels of VOC in the ready-to-use product (category II Af) are 150 g/l maximum in 2007 and 130 g/l maximum in 2010.

Particular provisions :

No data available.

Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):
<https://echa.europa.eu/substances-restricted-under-reach>.

> Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006: <https://echa.europa.eu/fr/authorisation-list>.

> Ozone-depleting substances (Regulation (EC) No 2024/590).

The mixture does not contain any substance posing a risk to the ozone layer.

Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):

The mixture does not contain a persistent organic pollutant.

> PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

15.2. Chemical safety assessment

This product contains at least one substance with an exposure scenario

The risk management measures (RMM) are included in the body of the Safety data sheet
use at ambient temperature

Maximum duration for individual exposure (Professionals):

Covers daily exposures up to 8 hours and 5 days per week

Maximum duration for individual exposure (Consumers):

Covers daily exposures up to 4 hours

>SECTION 16 : OTHER INFORMATION

> Wording of the phrases mentioned in section 3 :

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure .
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

> Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

EXTERIOR BARE WOOD PRIMER

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time-Weighted Average

VLE : Threshold Limit Value (exposure)

VME : Average Exposure Value.

ADR : Agreement concerning the international carriage of dangerous goods by road.

GHS07 : Exclamation mark

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

WGK : Water Hazard Class.

The information contained in this safety data sheet is based on our current knowledge at the time of publication and is provided in good faith. It does not constitute any guarantee of specific product properties nor establish any contractual relationship. The user remains solely responsible for safe and compliant use of the product in accordance with current regulations.

|> Modification compared to the previous version