

HARDWAXOIL

Quick-drying parquet oil with excellent wear-resistance. Good filling and good chemical and mechanical resistance. Can be used for various applications, such as floors, stairs, furniture and panels.

- » Gives the wood a rustic aspect.
- » Easy to apply.
- » Available in 16 colours and can be mixed with each other.



PROTECTION
INDOOR

1L

5L



PREPARATION

Make sure that all old finish coats are completely removed and that the wood is free from dust and other dirt. Sanding using the correct method : deep sanding with 60-80-100 grit then sanding with 100 grit. Can be used on sanded, planed, and brushed wood. When using HARDWAXOIL EFFECT BRONZE or METALLIC, its recommended to brush the floor beforehand and to apply first a dark colour (Aquastain black).

APPLICATION

Stir and shake well before and during use. Apply HARDWAXOIL evenly with a buffing machine, brush or cloth. Let the HARDWAXOIL settle and remove any excess oil within a few minutes by brushing it with a pad or cloth until the surface feels handdry. Hardwood like oak require 2 layers. Multiple layers can be applied for soft wood. For exotic wood types, the HARDWAXOIL should be tested beforehand. For industrial applications (rolling, spraying), the Ciranova® technical service should be consulted.

DRYING TIMES :

drying under standard conditions (20°C, 50%RH), is +/- 6 hours. For finishes with a high pigment content, the drying times under standard conditions (20°C, 50% HR), can be delayed to max. 12 hours. The drying times depend on the applied quantity, temperature, humidity and ventilation.

FINISHING

For finishes applied with a tinted oil, it is preferable to finish with a natural oil from the Ciranova range : HARDWAXOIL natural or HARDWAXOIL TITAN from the Ciranova range.

MAINTENANCE

For regular maintenance we recommend Ciranova® FLOORING SOAP. For periodic maintenance, use Ciranova® MAINTENANCE OIL or first use INTENSIVE CLEANER in case of heavy dirt. HARDWAXOIL is only fully hardened after +/- 7 days. During this period, the wood cannot be treated with water or maintenance products.

IMPORTANT INFORMATION ▲

Dried oil residue is self-igniting. Used pads and clothes must be submerged in water after use. The final color depends on the wood type, sanding, and the amount applied. **That is why it is recommended to always test the color beforehand!**

TECHNICAL DATA

Product type

solvent-based

Viscosity

+/- 300 sec (ISO n°3 at 20°C)

Solid content

+/-35 %

Gloss level

matt

Cleaning

Cleaning Thinner Ciranova®

Number of colors

16

Coverage

40-50 m²/liter per coat

Drying times

lightly walkable after: 24 hours
fully cured after: +/- 7 days
Highly pigmented colours extend the drying time.

Sanding grit

P 100-120

Storage/transport

between 5°C and 25°C

Disposal

dispose of residue and empty packaging in accordance with local ordinances.